

F2H-FPX-P10 Series ODF

Summary

F2H-FPX-P10 Series ODF is used as terminal equipment of fiber optic cable for optical fiber wiring, fixation, fusion and patching.

Features

- Adapters are installed in angle to avoid direct laser beam.
- Changeable adapter panel for SC, FC, LC, etc.
- Cable fixation and strength member fixation system on the left and right back of ODF.
- Excellent fiber bending radius mechanism to ensure minimum bending radius
- Very reasonable cable management
- Removable door and cover
- Drawer type ODF



General Specifications

Applicable Adapter	SC, FC, LC
Capacity	24 fibers
Material	cold rolled steel
Color	grey
Size	482.6(W)*365.5(D)*44(H)mm (19" 1U)
Net Weight	4.2kgs
Installation Method	19" rack mount
Splice Tray Capacity	24 fibers/tray

How to order a Grandway ODF

Model Rules: F2H-FPX-P10-XX-XX-XX

Ordering Information:

Model	Type	XX: Adapter	Fiber Capacity	XX: Pigtail
FPX	P10	SC: SC/UPC	24=24 fibers	SC: SC/UPC
		AS: SC/APC	48=48 fibers	AS: SC/APC
		LC: LC/UPC		LC: LC/UPC
		AL: LC/APC		AL: LC/APC
		FC: FC/UPC		FC: FC/UPC
		AF: FC/APC		AF: FC/APC