

F2H-FOSC-BDM-C5S24-6VG

Dome Type Mechanical Sealing Fiber Optic Splice Closure (FOSC)

Description:

F2H-FOSC-BDM-C5S24-6VG Dome Type Mechanical Sealing Fiber Optic Splice Closure (FOSC) is heat shrinkable sealing. The installation method can be wall mounting, pole mounting and manhole.

Specification:

Model	F2H-FOSC-BDM-C5S24-6VG
Type	Dome type
Outside dimension	435×230mm
Weight (excluding outside box)	3800~4300g
Number of inlet/outlet ports	5 pieces (4pcs of round ports and 1pc of oval uncut cable port)
Diameter of fiber cable	10~17.5mm for round ports and 10~17.5mm for oval uncut cable port
Capacity of FOSC	Bunchy: 24~144 (cores)
Body material	Modified polymer plastics
Assembling method	Wall mounting, pole mounting and manhole
Temperature	-40°C~65°C

Order Information:



Part Number	Description
F2H-FOSC-BDM-C5S24-1VG	24-core, 5-port
F2H-FOSC-BDM-C5S24-2VG	48-core, 5-port
F2H-FOSC-BDM-C5S24-3VG	72-core, 5-port
F2H-FOSC-BDM-C5S24-4VG	96-core, 5-port
F2H-FOSC-BDM-C5S24-5VG	120-core, 5-port
F2H-FOSC-BDM-C5S24-6VG	144-core, 5-port