

FTTH Drop Cable Type Fiber Optic Splice & Splitter Closure features with ruggedness, which is tested under harsh conditions and stand up to even the most severe conditions of moisture, vibration and extreme temperatures. Humanized design helps user get better experience and safer operating environment.

Features

1. Dis-mountable adaptor panel
2. Support midspan termination
3. Easy operation and installation
4. Rotatable and dis-mountable splice tray for easy splicing

Applications

1. Wall mounting & pole mounting installation
2. Suitable for 2*3mm Indoor FTTH Drop Cable and Outdoor Figure 8 FTTH Drop Cable

Specifications

Model	F2H-JCD-16-I4		F2H-JCD-24-I4	
Adapter	16pcs of SC		24pcs of SC	
Cable Ports	1 oval uncut port	2 round ports	1 oval uncut port	2 round ports
Applicable Cable Diameter	10~17.5mm	8~17.5mm	10~17.5mm	8~17.5mm
Drop Cable Ports	16 ports		24 ports	
Applicable Cable Diameter	2*3mm FTTH Drop Cable, 2*5mm Figure 8 FTTH Drop Cable and 4mm cable or 7mm cable			
Dimension	385*245*130mm		385*245*155mm	
Material	modified polymer plastic			
Sealing Structure	mechanical sealing			
Color	black			
Maximum Splicing Capacity	48 fibers (4 trays, 12 fibers/tray)			
Applicable Splitter	1pc of 1*16 PLC Splitter or 2pcs of 1*8 PLC Splitters			
Sealing	IP67			
Impact Test	IK10			
Pull Force	100N			
Midspan Entry	Yes			
Storage (Tube/Micro Cable)	Yes			
Net Weight	4kg			
Gross Weight	5kg			